




**UNICAM  
SYSTEMS**  
LEGITIMATE SECURITY GUARANTEED

*India's Most Trusted CCTV Brand*

## **UC-P553 E3-MAZ 5MP IR DOME NETWORK CAMERA**



- H.265S/H.265+/H.265/H.264S/H.254+/H.254/MJPEG coding
- Max. resolution: 2592 × 1944
- ICR auto switch, true day / night vision
- 30 ~ 50m IR night view distance
- Motorized zoom lens
- 3D DNR, true WDR, HLC, BLC, Defog, NIR, Smart IR and ROI coding
- Support image distortion correction
- Built-in micro SD card slot; up to 256GB
- DC12V/PoE power supply
- IP67 & IK10
- Support three streams
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS
- Intelligent analytics



[www.unicamsystems.com](http://www.unicamsystems.com)

Model	UC-P553 E3-MAZ			
<b>Specifications</b>				
<b>Camera</b>				
Image Sensor	1 / 2.7" CMOS			
Image Size	2592 × 1944			
Electronic Shutter	1 / 3 s ~ 1 / 10000 s			
Iris Type	DC Iris			
Min. Illumination	0.009 lux@F1.6,AGC ON; 0 lux with IR			
Lens	2.8~13.5mm@F1.4, motorized			
Field of View	Horizontal: 90°~31°; Vertical: 67°~24°; Diagonal: 115°~38°			
Lens Mount	Φ14			
Day & Night	ICR			
Wide Dynamic Range	120dB			
BLC	Yes			
HLC	Yes			
Defog	Yes			
Digital NR	3D DNR			
Angle Adjustment	Pan: 0°~345°; Tilt:0°~77°; Rotation: 0°~345°			
<b>Image</b>				
Video Compression	Main stream: H.265S / H.265+ / H.265 / H.264S / H.264+ / H.264 / MJPEG Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG			
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile			
Resolution	5MP (2592× 1944 ), 4MP (2592× 1520), 2K (2560× 1440), 3MP(2304× 1296 ),1080P (1920× 1080), 720P (1280× 720 ), D1, CIF, 480× 240			
Main Stream	5MP/4MP/2K/3MP/1080P / 720P( 60Hz : 1 ~ 30fps; 50Hz: 1~25fps ) HFR mode: 1080P / 720P( 60Hz : 1 ~ 60fps; 50Hz: 1~50fps )			
Sub Stream	720P/D1/CIF/480× 240( 60Hz : 1 ~ 30fps; 50Hz: 1~25fps )			
Third Stream	D1/CIF480 × 240 ( 60Hz : 1 ~ 30fps; 50Hz: 1~25fps )			
Bit Rate	64 Kbps ~ 8 Mbps			
Bit Rate Type	VBR / CBR			
Audio Compression	G711A / U			
Image Settings	ROI, Saturation, Brightness, Hue, Contrast, Wide Dynamic, Sharpness, Image Mirror, Image Flip, NR, etc. adjustable through client software or web browser			
ROI	Each ROI to be configured separately			
<b>Interfaces</b>				
Network	RJ 45			
Video Output	CVBS output (BNC × 1)			
Audio	1CH audio input; 1CH audio output; 1CH built-in MIC			
Storage	Built-in micro SD card slot; up to 256GB			
Reset	Yes			
Alarm	1CH alarm input; 1CH alarm output			
<b>Intelligent Analytics (Smart Events)</b>				
Perimeter Protection	Line crossing, region entrance/exiting/intrusion (human/motor vehicle/ non-motor vehicle classification)			
Statistics	Target counting by line/area, heat map			
Exception Detection	Scene change, video blur detection and video cast detection			
Face Detection	Face detection and face capture			
Other Events	Abandoned/missing object detection, crowd density detection			
<b>DORI Distance</b>				
Lens	Detect	Observe	Recognize	Identify
2.8~12mm(W)	58.7m(192.58ft)	23.5m(77.09ft)	11.7m(38.38ft)	5.9m(19.35ft)
2.8~12mm(T)	182.9m(600.06ft)	73.2m(240.15ft)	36.6m(120.07ft)	18.3m(60.03ft)
<b>Functions</b>				
Remote Monitoring	Web Browser/TVT NVMS2.0/NVR/mobile APP			
Web Browser	IE(plugin required)/Google Chrome/Edge/Firefox/Safari			
Online Connection	Support simultaneous monitoring for up to 10 users; Support multi-stream real time transmission			

Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, RTMP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPs, HTTP POST, QoS
Interface Protocol	ONVIF
Storage	Network remote storage; micro SD card storage
Smart Alarm	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection
General Function	Watermark, IP address filtering, video mask, heartbeat, password protection,image distortion correction, corridor pattern
PoE	Yes , IEEE802.3af
IR Distance	30 ~ 50 m
Ingress Protection	IP 67& IK10
<b>Others</b>	
Power Supply	DC12V/PoE
Power Consumption	< 9W
Operating Environment	- 30 °C ~ 60°C (-22°F~140°F); Humidity: less than95 % (non-condensing)
Storage Environment	- 30 °C ~ 65°C (-22°F~149°F), Humidity: less than 95 % (non-condensing)
Dimensions ( mm )	Φ 141 × 100.2
Weight ( net )	Approx. 0.93KG
Installation	Ceiling mounting; Wall mounting

## DIMENSIONS

